



Pool Equipment



SAND FILTER SERIES

LASER SYSTEM

LASER SYSTEM



7 Way dial valve

With inspection sight glass and pressure gauge.

Non-corrosive resin clamp

For simple installation and service of dial valve and filter components.

Blow molded tank with deep high capacity sand bed

Carries more debris and extends filter cycles.
The tank is corrosion-resistant and UV-resistant

Injection-molded, high quality base

Provides a non-corrosive and UV-resistant elevated surface for sturdy support of pump and filter.

Heavy-duty large capacity strainer basket

The internal ribs in the large strainer basket assure flow, even when filled with leaves and debris.

Run Dry

Patented air-cooled heat sink allows pump to run dry without damage to shaft seal.



MODELS	DIMENSIONS FILTRATION RATE OF 17 GPM / ft ²		DIMENSIONS 0.0157 - 0.0217 in SILICA SAND REQUIRED		FLOW RATE - US GPM		MAXIMUM TANK PRESSURE	WATER TEMPERATURE
	DIAMETER	SQ FT	LB	FILTER	BACKWASH	PSI (LB / PO ²)		
L160C	16"	1.33	140	23	17	50	95°F	
L192C	19"	1.87	200	32	24	50	104°F	
L225C	22.5"	2.64	250	45	34	50	104°F	
L250C	25"	3.30	350	56.1	42	50	104°F	



FILTRATION



BACKWASH



RINSE



WHIRLPOOL



DRAIN



TEST



WINTERIZE