LOOP-LOC MEASURING FORM

DEALER INFORMATION	SHIP TO:
DEALER CODE: DATE:	
COMPANY NAME:	ADDRESS:
ADDRESS:	CITY: STATE: ZIP:
CITY: STATE: ZIP:	ESTIMATE (Default if no box checked) ORDER USE CREDIT CARD ON FILE
JOB NAME:	ADDITIONAL INFORMATION For job previously submitted #
POOL TYPE: In-Ground On-Ground	Commercial Stock ID#
ULTRA-LOC SOLID GREEN	INS WITH AUTOMATIC COVER PUMP □GRAY □TAN
☐ REPLACEMENT COVER	☐ SPECIAL RECTANGLE (approximate 3' sections)
Brass Anchors	*Stainless Steel Anchors *Stainless Steel Masonry Anchor Collars composite decks) *Upcharge
Please note any additional hardware with quantities here:	



Please supply the name and address of consumer to be entered into our warranty database.

Name:		
Address:		
City:		
State:	Zip Code:	

COMPANY NAME:			JOB N	IAME/P.O.#:		
Pool Type: Inground Ongr	ound Manufacturer			* show varying o	leck sizes on sket	
Corner Type: Square	Radius	s Dimension		_ •	ength	
Are cut corners wanted? *cuts req'd for radii 4'+ and diag	Yes No	Obstruction		□ No tch & submit ques	ction nago	
				cir & Subillit ques	stion page	
Sketch of pool showing vary	ing deck levels &	any obstruction	ons			
Please check appropriate b	ox to indicate co	orrect pool sh	nape:			
A B Rectangle	C True L	F Left B	B True L		F Greci	A J
B J-D Roman E K H A If J or K are greater than 6' must be a Formfit	True 0		E G H	L Left	B L C	H J D
А	В С	D E	F G	н і	J K	L
Rectangle						
TrueL						
Grecian						
RomanEnd						
True Oval						
LazyL						
STEP or SWIMOUT: Note:				entered or if the	nere are obstru	ictions.
Roman Pools - sketch mus	t be done snowi					
90 corners		Diagona 3	ii Walis		True Radius R	oman
1 2		1/2			1	

STEP LOCATION: Centered: Yes - specify which wall step is located on _____

No - show location & offset on sketch on top.

2 = _____ 3 = _____ 1 = _____ 2 = _____

_	Α	В	, —	_ A		В,			.	В	, <u> </u>		Δ	В	_		A	١	В
			21				41				61_				66	3			
			22				42		\perp		62				67	7			
			23				43		\perp		63				68	3			
			24				44				64_				69	9			
			25				45		\perp		65_				70)			
L			26				46												
			27				47					<u>RE</u>	QUI	RED	<u>INFC</u>	RM	<u>IATI</u>	<u>ON</u> !	
			28				48					POII	NT TO	POINT	CROS	S DIN	MFNS	SIONS	
L			29				49		\perp		PT		to P	Т	PT.		1	to PT	
L			30				50				Dista	nce = _			_ Dist	tance	e =		
L			31				51		\perp		PT Dieta	nco -	to P	Г	PT.	anco	¹	to PT.	
L			32				52				Dista	1100		CKING					
L			33				53		\perp		Deck	Width	(inclu	ding co	ping)_				
			34				54					**in	dicate	areas I	ess tha	an 3'	on sl	ketch*	*
			35				55				Loop-	Loc Pip	es War	nted For	Entire	Cover	r? [] YES	□ N
T			36				56							<u>PC</u>	OL TY	PE_			
I			37				57] 🗆 (Gunite		Packa	ge Ma	anufa	cture	e	
			38				58				What	Is Cori	ner Ra	ndius?.					
			39				59				What	Is Diag	jonal (Corner Corners	Length	? _	_	NO	
Ť			40				60												ater thar
N	 IUST BE 3'	BACK FROM	POOLINE	• PROVIDE	INSIDE	 POOL D	MENSIO	ONS INC	LUDING	STEP SIZ		 OCATION	. N• SH0	. 	TION OF	. 	 ITS "A	— · — · \" & "B'	
		BACK FROM W ALL OBST																	IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA
																			IN RELA

** DISTANCE FROM POINT "A" TO POINT "B" = _____Ft. ____In. **

[&]quot;A-B" Measurements cannot be used unless this <u>distance</u> is given! Distance should be at least 2/3 the length of the pool.

Cor	ntact:			Dealer/Company Name:
Job	Name:/P.O.#:			Phone# Fax#
<u>0B</u>	STRUCTIONS: CHECK ONE	YES	NO	DECKING & COPING: CHECK ONE YES NO
1.	Are there any non-removable handrails, grabrails, or ladders? a. "A-B" dimensions are required to front center of all rails, blocks, cups, and to the points where rails dip below coping. b. Distance rails extend into pool Distance rails are set back from pool Type of grabrail: Rail Concrete block/Anthony type			9. Coping Width Coping Material a. Is coping rough?
2.	Are there any raised rail sockets?			11. Deck Material: please show on sketch if deck type varies a. Wood: Loop-Loc Wood Deck anchors wanted?
3.	 b. Height of sockets (3" or higher require cutout.) Are there any grab rocks?			b. Composite Deck: Deck-Loc anchors wanted?
4.	b. Width of each grab rock Distance grab rocks are set back from pool Is there a non-removable fillspout?			d. Planters or Grass Areas: Loop-Loc Pipes wanted for anchor in pipe installation? Overlap wanted in planter area (minimum 9" for safety) 12. Auto Cover box?
	If raised, how high? Distance set back from pool c. Is end of spout below coping? Distance into pool Distance below coping level			b. Is cover box raised? If yes, how high c. Dividing wall between waterline and coverbox? Width RAISED AREAS: PHOTOS REQUIRED 13. For safety cover, verify all raised wall areas are strong enough for cover to attach to it with wall anchors and o-rings
5.	Is there a dive stand?			b. Height of Raised area c. A-B the beginning, the end, the front and sides of the raised area where cover is to be attached, as well as the pool wall, at 1' intervals.
6.	b. Is LOOP-LOC Dive Stand Kit required?			Note start & end points below: Begins @ pt # Ends @ pt # Begins @ pt # Ends @ pt # Begins @ pt # Ends @ pt # Begins @ pt # Ends @ pt # d. Waterfall or Rock formations - need distance rocks overhang pool edge
	b. Distance rock overhangs pool edgeDistance rock extends below deck levelc. Height of rock			VARYING DECK LEVELS: PHOTOS REQUIRED 14. A-B location for each rise, A-B each level including points on risers to show angle away from pool edge. 25. **The control of the control
	Are there slide legs within 2' of pool?			Pt #height Pt #height Pt #height Pt #height Pt #height Total Height If there are raised areas or varying deck levels select treatment wanted:
	PA INFORMATION: PHOTOS REQUIRED Is there a spa? Coping width			Raised Wall Treatment Up & Over Treatment Protect-A-Gap with Cable & Cable Kit (Maximum Rise 9") (Rises over 9")
	a. Is spa to be included in this estimate/order?			NEGATIVE EDGE/OVERFLOW POOLS: PHOTOS REQUIRED 15. Is basin to be included in this estimate/order?
(If yes, how high? c. Can anchors be installed on the outside spa wall? For Safety 18" height or greater cover must be designed to anchor into spa side of d. Is spa dividing wall flush with top of coping? "A-B" Dimensions required on both Spa & Pool side of wall. e. Does spa wall have an open spillway?	wall)		ONGROUND POOLS: 16. Are there varying deck sizes? (If yes, submit sketch)
	If yes, "A-B" dimensions are required to locate spillway. f. If solid w/drains, is drain panel wanted in spa area? g. Are there any other specific spa cover design instructions? Please specify!			Pool type: Skimmer Exposed Gutter Gutter width **Measure to deck edge & indicate location of gutter on sketch** 17. Are there any specific design instructions? Please specify

MEASURING INSTRUCTIONS

- 1. Begin with a freehand sketch indicating inside pool dimensions. Include deck area, planters and any obstructions within 3' of the waterline. A photo of the pool is needed when rocks, waterfalls, raised walls, spas or *anything* out of the ordinary exists.
- 2. Establish two points, "A-B" with "A" on the left as shown. "A-B" line must be at least 3' away from the pool and 2/3 the length of the pool; 20'-25' is typical (show this on the sketch). To mark "A-B" points on deck use chalk marks, on ground use stakes in the dirt.

NOTE: The "A-B" line **must never** cross the pool line and should be approximately 3' away from the pool at the closest point (4' to 5' away for pools over 44' long).

- 3. Using chalk, mark and number points along the inside edge of the pool at approximately 3' intervals. Number all corner points, ladders, handrails, grabrails, slide legs, rocks, spillways, spa walls separating spa and pool, fill spout and dive stand. 1' to 2' intervals should be used in small or tight radius areas. For raised area, points should be taken to the beginning, the end, the front and the sides of raised area where cover is to be attached, as well as the pool wall at 1' intervals. Straight walls should have at least 3 points, beginning, middle and end.
- 4. Measurements are now taken from point "A" to point #1, then point #2, and all the way around the pool. Then measure from point "B" to same point #1 and then #2, as you did for point "A". Measurements are listed in column format as shown.
- 5. Take measurements **between 2 known points** to determine the **length and width** of the pool. Additional measurements for difficult pools are suggested. Cross dimensions to any raised beam obstacles are also recommended.
- * Replacement Covers A-B line should be 3' back from anchors. Same A-B line should be used for both pool and anchors whenever possible. If same A-B line not possible, common A-B points and the relationship between the 2 different A-B lines must be shown. Please use Loop-Loc's replacement/alteration measuring form.

		_		
2	15'-8	3"	31'-	-7"
2 3 4	17'-0)"	34'-	-6"
4				L
5				L
6				L
7				L
8				
9				
10	OE		Щ	
11	\supseteq			
12				L
13	ONTINE		Z	
14	0		$\frac{1}{2}$	
15				
16				
17				
18				
19				
20	1		,	V

B

NO.

14'-3'



