



ALUMINUM SUBMERSIBLE UTILITY PUMPS

DEWALT UTILITY PUMPS are engineered to be contractor tough and deliver the performance you demand. Bring the pump that gets the job done.



DXWPUTILITY

GUARANTEED TOUGH.®

SUBMERSIBLE UTILITY PUMP

1-1/2 IN. FPT DISCHARGE

Easy installation in new and existing applications.

THERMAL OVERLOAD PROTECTION

Prevents possible overheating and damage to motor.

HIGH FLOW IMPELLER

For maximum performance.

CARRY HANDLE

Easy to transport and install.

ROBUST MATERIALS

Engineered to be durable, reliable and high performing

3/4 IN. GHT ADAPTER

For use with standard garden hose.



Ideal For Pools and Hot Tubs

SPECIFICATIONS

MATERIAL	Aluminum
IMPELLER TYPE	Thermoplastic Impeller
SOLIDS HANDLING	Up to 3/8 in. Diameter
DISCHARGE SIZE	3/4 in. GHT or 1-1/2 in. FPT
RUNNING AMPS BY HP	4.8 - 8.3
CORD LENGTH	20 ft.
VOLTAGE	120 Volt AC



Pump Dimensions

PERFORMANCE - GPM AT HEIGHT

Model	HP	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.	25 ft.	30 ft.
DXWP61374	1/3	58	53	50	43	33	25	18
DXWP61774	3/4	83	77	73	65	55	45	33

PUMP WARRANTY

10
YEAR
LIMITED
WARRANTY

PUMP INCLUDES

- (1) Submersible Utility Pump
- (1) 3/4 in. GHT x 1-1/2 in. MPT Adapter
- (1) Owners Manual

#99620 50' X 1-1/2" LAY FLAT HOSE KIT



DEWALT®, GUARANTEED TOUGH® and the yellow/black color scheme are trademarks for DEWALT power tools, outdoor equipment, accessories, anchors and concrete adhesives and are used under license. Product may differ from that pictured. Does not affect function. Manufactured under license by: PEDROLLO GROUP INC. | 45 MARYLAND AVE EAST | ST. PAUL, MN 55117



DXWPUTILITY
Form 602500 Rev: 06/18/24

GUARANTEED TOUGH.®

1-855-222-3841
customer.service@pedrollo-usa.com

www.DEWALT.com